

Bike tire belt

 Low-tech with Refugees - Low-tech & Réfugiés



https://wiki.lowtechlab.org/wiki/Ceinture_en_pneu_de_v%C3%A9lo/en

Dernière modification le 15/11/2024

 Difficulté Moyen

 Durée 30 minute(s)

 Coût 0.50 EUR (€)

Description

DIY bike tire belt

Sommaire

Sommaire

Description

Sommaire

Introduction

Étape 1 - Creat the belt strap

Étape 2 - Creat the belt buckle

Étape 3 - Install and secure the belt buckle on the strap.

Étape 4 - Install and secure the belt loop

Étape 5 - Create the belt notches

Commentaires

Introduction

In this DIY, we will explain how to create a belt made from an old bike tire.

Matériaux

- Bike tire (one per belt) - belt buckle or wire - bike inner tube - screw rivet (or pop rivet)

Outils

- Scissors - Cutter - Hole punch - Metal pliers - Riveter (if using pop rivets)

Étape 1 - Create the belt strap

Cut the part of the tire which will constitute the belt, to the desired length, taking a model from an old belt or taking its waist measurement and adding approximately 15 cm.



Étape 2 - Create the belt buckle

Re-use a buckle from an old belt.

or

Create the buckle and pin of the belt from a metal rod using metal pliers.

If the buckle is not welded, the rod junction point must not be centered, otherwise the barb will come out.


Étape 3 - Install and secure the belt buckle on the strap.

At 10 cm from the edge, fold one end of the strap and drill a hole in the middle. This hole will allow the tongue to pass through. Install the buckle and pass the rod through the hole. Fold the tire around the buckle To hold the buckle in place, create a hole about one centimeter from the buckle in the middle, then rivet, adding a washer to hold the rivet (or use a pop rivet). If the tire is thick, drill two holes on either side of the strap.



Étape 4 - Install and secure the belt loop

Install the inner tube loop, by sliding it along the strap. To possibly fix the loop, put a last screw rivet (or pop rivet) after the buckle to hold it securely.



Étape 5 - Create the belt notches

Take measurement to choose where to put the belt notches.
Make holes with the hole punch pliers to form the notches of the belt.
The belt is ready!!

